

VEHICLE MODEL	MINI AGRI 26.6	APOLLO 26.6
MAXIMUM CAPACITY	2600 kg (5732 lb)	2600 kg (5732 lb)
Maximum Lifting Height	5,73 m (18,8 ft)	5,73 m (18,8 ft)
MAX SPEED	30 km/h (18,6 mph)	30 km/h (18,6 mph)
UNLADEN WEIGHT	5100 kg (11244 lb)	5100 kg (11244 lb)
ENGINE	KUBOTA	YANMAR
NOMINAL POWER	55 kW (74 HP)	53,7 kW (72 HP)
@RPM	2600 rpm	2500 rpm
HYDRAULIC PUMP CAPACITY	80 l/min (21,1 gal/min)	80 I/min (21,1 gal/min)

Data refers to the CE market only









Data refers to the CE market only.

For all other markets, scan the QR code









## APOLLO | MINI AGRI

The ideal telehandler for working in tight spaces, thanks to the perfect combination of great power and extreme maneuverability. Unrivaled fluidity of movement and millimetric precision in small movements.

**Pneumatic suspension on the boom** reduces oscillations to a minimum.

The **3 steering modes** – front, concentric, transverse – allow **smooth driving** even with the heaviest loads.



- **Arm too high** function: travel speed limited automatically when the boom is raised.
- Soft Motion system: boom movements more easy to control, with reduced movement speed when using the basket and in pre-alarm conditions.
- Anti-tipping system: aggravating movements blocked in the event of overload and load level always in evidence.
- Double-cylinder, double-action **hydraulic accessories lock** for maximum stability.
- Rops and Fops Cab: operator protection guaranteed thanks to the dimensional stability of the cab.





## TECHNOLOGICAL EFFICIENCY

- Single-speed hydrostatic transmission: best speed-power ratio maintained in all working conditions.
- Electronic accelerator and Inching pedal: accurate and controlled movement at any speed, even with the boom at full power.
- Creeper function\*: adjustable forward speed with the accelerator pedal, constant engine speed and oil flow rate to effectively use equipment such as sweepers or straw spreaders.
- Telematics kit, DTS, for remote machine monitoring.
- \* Not available for EXTRA-CE models



## EASY AND INTUITIVE

- New single-lever CAN-bus joystick, which also incorporates the direction selector (reverse shuttle - FNR) for intuitive and comfortable proportional control.
- Single-lever Proportional and Flow Sharing distributors: more simultaneous movements and better response to commands.
- Continuous oil function as standard.
- · Automatic equipment recognition.

## TOTAL COMFORT

- **Total comfort** through **acoustic soundproofing**, adjustable steering wheel, radio, sun screens, cushioned and ergonomic suspension seat.
- **New 7" display:** clear and immediate viewing of the information needed to operate the vehicle.
- The semi-automatic air conditioning system allows perfect air circulation inside the cabin.
- LED work lights on the cab and on the boom, for maximum visibility even at night.
- Rear-view mirrors that allow all-round visibility of the vehicle and **optional cameras** for challenging maneuvers.

